











Articulated Dumper Range

PRICE LIST 2019
CENTRAL EUROPE - EN



D 100 - 120 - 150 A

REF	CHARACTERISTICS	MAX. CAPACITY	TRANSMISSION	ENGINE	EUR
M706 	D 100 AHA Front and hi-tipping up to 1.6 m / 63 in Machine (L x W x H): 3,190 x 1,100 x 2,560 mm/126 x 43 x 101 in Permanent 4WD. Tyres 27x8 50-15".	load: 1,000 kg / 2,200 lb Water: 345 l / 0.45 cu vd Struck: 395 l / 0.51 cu vd Heaped: 565 l / 0.73 cu vd	Hydrostatic	KUBOTA 20.9 HP / 16.8 kW	29.360
M706 + 661.10 	D 100 AHA COMPACT Front and hi-tipping up to 1.6 m / 63 in Machine (L x W x H): 3,190 x 990 x 2,560 mm/126 x 39 x 101 in Permanent 4WD. Tyres 6,5/80-12. (Total machine width <1 m)	load: 1,000 kg / 2,200 lb Water: 345 l / 0.45 cu vd Struck: 395 l / 0.51 cu vd Heaped: 565 l / 0.73 cu vd			28.800
M707 	D 100 AHG 180° rotating skip. Machine (L x W x H): 3,190 x 1,100 x 2,560 mm/126 x 43 x 101 in Permanent 4WD. Tyres 27x8 50-15".	load: 1,000 kg / 2,200 lb Water: 325 l / 0.42 cu vd Struck: 390 l / 0.51 cu vd Heaped: 545 l / 0.71 cu vd			29.360
M710 	D 120 AHA Front and hi-tipping up to 1.7 m / 66 in Machine (L x W x H): 3,190 x 1,200 x 2,610 mm/126 x 47 x 103 in Permanent 4WD. Tyres 10.0/75-15.3".	load: 1,200 kg / 2,645 lb Water: 425 l / 0.55 cu vd Struck: 515 l / 0.67 cu vd Heaped: 700 l / 0.91 cu vd			29.720
M711 	D 120 AHG 180° rotating skip. Machine (L x W x H): 3,190 x 1,195 x 2,610 mm/126 x 47 x 103 in Permanent 4WD. Tyres 10.0/75-15.3".	load: 1,200 kg / 2,645 lb Water: 415 l / 0.54 cu vd Struck: 495 l / 0.64 cu vd Heaped: 695 l / 0.90 cu vd			29.720
M713 	D 150 AHA Front and hi-tipping up to 1.7 m / 66 in. Machine (L x W x H): 3,180 x 1,480 x 2,610 mm/125 x 58 x 103 in Permanent 4WD. Tyres 10.0/75-15.3".	load: 1,500 kg / 3,300 lb Water: 605 l / 0.79 cu vd Struck: 681 l / 0.89 cu vd Heaped: 841 l / 1.09 cu vd			30.210
M712 	D 150 AHG 180° rotating skip. Machine (L x W x H): 3,245 x 1,470 x 2,560 mm/128 x 58 x 101 in Permanent 4WD. Tyres 10.0/75-15.3".	load: 1,500 kg / 3,300 lb Water: 520 l / 0.68 cu vd Struck: 626 l / 0.81 cu vd Heaped: 900 l / 1.17 cu vd			30.210

STANDARD EQUIPMENT: Hydraulic steering, exclusive AUSA epicyclic reduction axles, ergonomic and adjustable seat, retractable seat belt, total control of movements with joystick, foldable ROPS roll bar, watertight hydraulic brakes, rotating beacon, rear-view mirror, anti-vandal protection and audible reverse warning.

DRIVING POSITION		
321.80	FOPS protective roof over the folding ROPS arch. (NOT compatible with the backwards folding arch).	310
767.00	Backwards folding ROPS Arch.	1.570
SAFETY		
744.03	Emergency stop on controls dashboard.	250
664.10	Disabling switch warning acoustic reverse.	110
698.05	Reflective safety adhesives on rear body.	160
747.00	Adhesive plates 25KM/H.	30
LIGHTING AND CIRCULATION		
319.00	Homologated lighting system.	940
470.63	GERMANY circulation regulation - Homologated lighting system included.	2.030
742.00 D 150 AHG	ITALY circulation regulation - Homologated lighting system included.	1.840
742.01 - AHA -	AUSTRIA circulation regulation - Homologated lighting system included.	1.390
742.01 - AHG -		
COMFORT		
526.03	Great comfort seat with total regulation.	530
ACCESSORIES		
711.00	Engine canopy Heavy duty metal engine canopy.	870
670.00	Documents Water-tight case for operation and maintenance manuals.	160
619.50	Towing Towing hitch (ball & pin) with electric socket.	910
ACOL	Paint Special paint colour (only parts in orange).	1.070
646.22	Environment Bio Hydraulic Fluid environmentally friendly.	990

ADHESIVE LANGUAGE AND MANUALS		
463.30 - AHA -	Adhesive plates in English.	0
463.41 - AHG -		
463.31 - AHA -	Adhesive plates in French.	0
463.42 - AHG -		
REGIONAL REGULATIONS		
D 100 - 120 - 150 AHA		
463.36	UK finish.	210
463.64 - AHA -	French finish - Disabling switch warning acoustic reverse INCLUDED.	70
463.32	German finish.	0
D 100 - 120 - 150 AHG		
	Italian finish.	
463.64	UK finish.	210
463.66	French finish - Disabling switch warning acoustic reverse INCLUDED.	70
463.62 - AHG -	German finish.	0
468.70	Polish finish - Only for D 150 AHG.	90
463.71	Sweden finish - Only for D 150 AHG.	150
463.70	Denmark finish - Only for D 150 AHG.	90
PARTS		
777.76	Maintenance kit (1000h).	160
800.21	Spare wheel (1ut) - Standard.	510
800.17 - D 100 AHA -		


D 250 - 350 - 450 A

REF	MAX. CHARACTERISTICS	MAX. CAPACITY	TRANSMISSION	ENGINE	EUR
M654	D 250 AHG 180° rotating skip. Machine (l x W x H): 4,035 x 1,770 x 2,905 / 159 x 70 x 114 in Permanent 4WD. Tyres 10.0/75-15.3	Load: 2,500 kg/5,500 lb Water: 720 l / 0.94 cu yd Struck: 1,330 l / 1.73 cu yd Heaped: 1,560 l / 2.04 cu yd	2 speed hydrostatic	KUBOTA 48.9 HP / 36.5 kW	41.650
M651	D 350 AHG 180° rotating skip. Machine (l x W x H): 4,180 x 1,845 x 2,930 mm / 165 x 73 x 115 in Permanent 4WD. Tyres 11.5/80-15.3 (14 PR)	Load: 3,500 kg/7,700 lb Water: 1,020 l / 1.33 cu yd Struck: 1,790 l / 0.55 cu yd Heaped: 2,130 l / 0.73 cu yd			42.660
M656	D 450 AHG 180° rotating skip. Machine (l x W x H): 4,390 x 1,866 x 2,935 mm / 173 x 73 x 116 in Permanent 4WD. Tyres 12,0/75-18	Load: 4,500 kg/9,920 lb Water: 1,370 l / 1.79 cu yd Struck: 2,055 l / 2.68 cu yd Heaped: 2,670 l / 3.49 cu yd			46.200

STANDARD EQUIPMENT: Watertight hydraulic brakes. hydraulic steering. ergonomic and adjustable seat. retractable seat belt. total control of movements with joystick. foldable ROPS roll bar. rotating beacon. rear-view mirror. anti-vandal protection and audible reverse warning.

DRIVING POSITION		
743.01	Homologated ROPS/FOPS driver protective folding roof.	1.210
SAFETY		
744.01	Emergency stop on controls dashboard.	260
664.00	Disabling switch warning acoustic reverse.	110
745.50	Full visibility System through (FVS) front and rear cameras and TFT water-proof color 7" display for a total visibility and nightvision by infrared up to 10 m and obstacle sensors. (International metric system).	1.890
752.00	Reflective safety adhesives on rear body.	170
747.01	Adhesive plates 25KM/H.	30
LIGHTING AND CIRCULATION		
319.20	Homologated lighting system.	1.600
470.62	GERMANY circulation regulation - Homologated lighting system included.	2.030
470.24	SWITZERLAND circulation regulation - Homologated lighting system included.	2.030
470.80	ITALY circulation regulation - Homologated lighting system included.	3.450
COMFORT		
526.02	Great comfort seat with total regulation.	710
ACCESSORIES		
690.31	Northern countries Specification for northern countries (more powerful heater. antifreeze and oil for low temperature and fuel filter water).	150
670.06	Documents Water-tight case for operation and maintenance manuals.	170
619.81	Towing Towing hitch (Rockinger).	1.010
620.30	Electric take-off for towing - COMPULSORY lighting system.	290
535.20	Protector Front rubber fender.	330
603.27	Filter Diesel filter decanter water.	210
ACOL	Paint Special paint colour (only parts in orange).	1.070
646.20	Environment Bio Hydraulic Fluid environmentally friendly.	1.450
TRANSPORT		
999.99	Photos for customs.	0
ADHESIVE LANGUAGE AND MANUALS		
465.59	Adhesive plates in English.	0
467.18	Adhesive plates in French.	0
REGIONAL REGULATIONS		
467.04	French finish - Disabling switch warning acoustic reverse INCLUDED.	70
465.68	UK finish.	0
465.66	German finish.	0
468.75	Italian finish.	70
468.97	Polish finish.	70
PARTS		
777.75	Maintenance kit (1000h).	450
800.08 - D 250 AHG -	Spare wheel (1ut) - Standard.	570
800.05 - D 350 AHG -		760
800.32 - D 450 AHG -		1.310

D 601 AHG Hydrostatic Dumper (DEUTZ TIER 4 & IIIB)

REF	CHARACTERISTICS	MAX. CAPACITY	TRANSMISSION	ENGINE	EUR
M6600	 D 601 AHG 180° rotating skip. Machine (L x W x H): 4.910 x 2.206 x 3.256 mm / 193 x 87 x 128 Permanent 4WD. Max. Speed 25 Km/h Tyres 405/70-20" (14 PR)	load: 6.000 kg / 13.000 lb Water: 1.665 l / 2.17 cu yd Struck: 2.455 l / 3.21 cu yd Heaped: 3.154 l / 4.12 cu yd	Hydrostatic	DEUTZ 55.4 kW with DOC (Diesel Oxidation Catalyst) common-rail/turbo- intercooler Final Tier 4/Stage IIIB- EU (97/68EC)	64.660

STANDARD EQUIPMENT: Negative watertight parking brake on front axle, self-locking differential on both axles, automatic ECO MODE function, hydraulic steering, fold down ROPS protective arch with folding assisted system by means gas spring, ergonomic and adjustable seat, retractable seat belt, total control of movements with joystick integrating main functions, rotating beacon, rear-view mirror, emergency stop, anti-vandal protection and audible reverse warning.

SAFETY		
6600.01	Disabling switch warning acoustic reverse.	110
6600.20	Full visibility System through (FVS) front and rear cameras and TFT water-proof color 7" display for a total visibility and nightvision by infrared up to 10 m and obstacle sensors. (International metric system).	1.890
6600.31	Second rear-view mirror.	250
LIGHTING AND CIRCULATION		
6600.00	Homologated lighting system.	1.640
6600.50	GERMANY circulation regulation - Homologated lighting system included.	2.030
ADVANCED EQUIPMENT		
6600.25	Smart/stop.	590
ACCESSORIES		
6600.32	Documents Water-tight case for operation and maintenance manuals.	170
6600.30	Towing Towing hitch (Rockinger) with electric take-off.	1.040
REGIONAL REGULATIONS		
6600.10	French finish - Disabling switch warning acoustic reverse INCLUDED.	0
6600.11	UK finish.	0
	Germany finish.	0
PARTS		
800.35	Spare wheel (1ut) - Standard.	1.290

D 600 A

REF	CHARACTERISTICS	MAX. CAPACITY	TRANSMISSION	ENGINE	EUR
M6413	D 600 AP (DEUTZ TIER 4 & STAGE IIIB) Hydraulic front tipping. Machine (L x W x H): 4,525 x 2,170 x 3,130 mm / 178 x 85 x 123 in Permanent 4WD. Tyres 405/70-20" (14 PR)	Load: 6,000Kg / 13,300 lb Water: 1,950l / 2.55 cu yd Struck: 2,650l / 3.46 cu yd Heaped: 3,290l / 4.30 cu yd	Torque converter with semi-synchronized 4-gear gearbox.	DEUTZ with DOC 75 HP / 55.4 kW (Final TIER 4 Stage IIIB-EU) 97/68EC	56.520
M6411	D 600 AP PLUS (DEUTZ TIER 4 & STAGE IIIB) Hydraulic front tipping. Machine (L x W x H): 4,525 x 2,170 x 3,130 mm / 178 x 85 x 123 in Permanent 4WD. Negative parking brake on front axle Limited slip differential in both axels. Tyres 405/70-20" (14 PR)				59.370
M6410	D 600 AP PLUS (KUBOTA TIER 4 & STAGE IIIB) Hydraulic front tipping. Machine (L x W x H): 4,525 x 2,170 x 3,130 mm / 178 x 85 x 123 in Permanent 4WD. Negative parking brake on front axle Limited slip differential in both axels. Tyres 405/70-20" (14 PR)			KUBOTA with DPF 113 HP / 83.5 kW (Final TIER 4 Stage IIIB-EU) 78/68EC	58.510
M6403	D 600 APG (DEUTZ TIER 4 & STAGE IIIB) 180° rotating skip. Machine (L x W x H): 4,640 x 2,170 x 3,130 mm / 180 x 85 x 123 in Permanent 4WD. Tyres 405/70-20" (14 PR)	Load: 6,000 Kg/13,300 lb Water: 1,565l / 2.04 cu yd Struck: 2,360l / 3.08 cu yd Heaped: 3,130l / 4.09 cu yd		DEUTZ with DOC 75 HP / 55.4 kW (Final TIER 4 Stage IIIB-EU) 97/68EC	58.610
M6401	D 600 APG PLUS (DEUTZ TIER 4 & STAGE IIIB) 180° rotating skip. Machine (L x W x H): 4,640 x 2,170 x 3,130 mm / 180 x 85 x 123 in Permanent 4WD. Negative parking brake on front axle Limited slip differential in both axels. Tyres 405/70-20" (14 PR)				61.670
M6400	D 600 AP PLUS (KUBOTA TIER 4 & STAGE IIIB) 180° rotating skip. Machine (L x W x H): 4,640 x 2,170 x 3,130 mm / 180 x 85 x 123 in Permanent 4WD. Negative parking brake on front axle Limited slip differential in both axels. Tyres 405/70-20" (14 PR)			KUBOTA with DPF 113 HP / 83.5 kW (Final TIER 4 Stage IIIB-EU) 78/68EC	60.770

STANDARD EQUIPMENT: Hydraulic steering, fold down ROPS protective arch with folding assisted system by means gas spring, ergonomic and adjustable seat, retractable seat belt, watertight hydraulic brakes, total control of movements with joystick, rotating beacon, rear-view mirror, anti-vandal protection and audible reverse warning.

DRIVING POSITION			
743.00	Homologated ROPS/FOPS driver protective folding roof. Folding assisted by gas springs.	1.210	
538.36	Full-Equip closed ROPS/FOPS cabin with heating including enhanced sound-proof and panoramic view	10.830	
538.32			
SAFETY			
744.02	Emergency stop on controls dashboard.	260	
664.01	Disabling switch warning acoustic reverse.	100	
745.51	Full visibility System through (FVS) front and rear cameras and TFT water-proof color 7" display for a total visibility and nightvision by infrared up to 10 m and obstacle sensors. (International metric system).	1.890	
698.10	Reflective safety adhesives on rear body.	170	
LIGHTING AND CIRCULATION			
319.10	Homologated lighting system.	1.640	
759.00	Max. 20 km/h speed limitation.	200	
470.28	AUSTRIA circulation regulation - Homologated lighting system included.	3.340	
470.19	GERMANY circulation regulation - Homologated lighting system included.	2.030	
470.20	SWITZERLAND circulation regulation - Homologated lighting system included.	2.030	
COMFORT			
526.04	Great comfort seat with total regulation.	690	
ACCESSORIES			
670.01	Documents	Water-tight case for operation and maintenance manuals.	170
619.80	Towing	Towing hitch (Rockinger).	1.040

620.30		Electric take-off for towing - COMPULSORY lighting system.	300
535.21	Protector	Front rubber fender.	330
696.20		Fan grid.	220
741.11	Air filter	Ciclonic air filter.	190
ACOL	Paint	Special paint colour (only parts in orange).	1.070
646.10	Environment	Bio Hydraulic Fluid environmentally friendly.	1.980
TRANSPORT			
999.99		Photos for customs.	0
ADHESIVE LANGUAGE AND MANUALS			
465.72		Adhesive plates in English.	0
467.14 - Deutz -		Adhesive plates in French.	0
467.09 - Kubota -			0
REGIONAL REGULATIONS			
D 600 A - DEUTZ			
467.11		French finish - Disabling switch warning acoustic reverse INCLUDED.	70
465.58 - Deutz -		German finish.	0
465.92		UK finish.	0
465.58		Swiss finish.	0
468.76		Polish finish - Only for APG model.	70
D 600 A - KUBOTA			
467.02		French finish - Disabling switch warning acoustic reverse INCLUDED.	70
465.71 - Kubota -		German finish.	0
465.85		UK finish.	0
465.71		Swiss finish.	0
465.94		Polish finish - Only for APG model.	70
PARTS			
800.10		Spare wheel (1ut) - Standard.	1.290
777.74 - Deutz -		Maintenance kit (1000h).	570
777.73 - Kubota -			

D 1000 A

REF	CHARACTERISTICS	MAX. CAPACITY	TRANSMISSION	ENGINE	EUR
M6323 	D 1000 AP (DEUTZ TIER 4 & STAGE IIIB) Hydraulic front tipping. Machine (L x W x H): 4,565 x 2,425 x 3,500 mm / 180 x 95 x 138 in 4RM permanente. Tyres 500/60-22.5" (16PR")	Load: 10,000 Kg / 22,000 lb Water: 2,440l / 3.19 cu yd Struck: 3,750l / 4.90 cu yd Heaped: 5,225l / 6.83 cu yd	Torque converter with semi-synchronized 4-gear gearbox. Permanent 4WD	DEUTZ with DOC 75 HP / 55.4 kW (Final TIER 4 Stage IIIB-EU) 97/68EC	67.160
M6321 	D 1000 AP PLUS (DEUTZ TIER 4 & STAGE IIIB) Hydraulic front tipping. Machine (L x W x H): 4,565 x 2,425 x 3,500 mm / 180 x 95 x 138 in 4RM permanente. Negative parking brake on front axle Limited slip differential in both axels. Tyres 500/60-22.5" (16PR")				70.130
M6320 	D 1000AP PLUS (KUBOTA TIER 4 & STAGE IIIB) Hydraulic front tipping. Machine (L x W x H): 4,565 x 2,425 x 3,500 mm / 180 x 95 x 138 in 4RM permanente. Negative parking brake on front axle Limited slip differential in both axels. Tyres 500/60-22.5" (16PR")			KUBOTA with DPF 113 HP / 83,5 kW (Final TIER 4 Stage IIIB-EU) 78/68EC	69.110
M6313 	D 1000 APG (DEUTZ TIER 4 & STAGE IIIB) 180° rotating skip. Machine (L x W x H): 4,775 x 2,425 x 3,515 mm / 188 x 95 x 138 in 4RM permanente. Tyres 500/60-22.5" (16PR")	Load: 10,000 Kg/22,000 lb Water: 1,950l / 2.55 cu yd Struck: 3,140l / 4.10 cu yd Heaped: 4,790l / 6.26 cu yd		DEUTZ with DOC 75 HP / 55.4 kW (Final TIER 4 Stage IIIB-EU) 97/68EC	70.310
M6311 	D 1000 APG PLUS (DEUTZ TIER 4 & STAGE IIIB) 180° rotating skip. Machine (L x W x H): 4,775 x 2,425 x 3,515 mm / 188 x 95 x 138 in 4RM permanente. Negative parking brake on front axle Limited slip differential in both axels. Tyres 500/60-22.5" (16PR")				73.310
M6310 	D 1000 APG PLUS (KUBOTA TIER 4 & STAGE IIIB) 180° rotating skip. Machine (L x W x H): 4,775 x 2,425 x 3,515 mm / 188 x 95 x 138 in 4RM permanente. Negative parking brake on front axle Limited slip differential in both axels. Tyres 500/60-22.5" (16PR")			KUBOTA with DPF 113 HP / 83,5 kW (Final TIER 4 Stage IIIB-EU) 78/68EC	72.240

STANDARD EQUIPMENT: Hydraulic steering, fold down ROPS protective arch with folding assisted system by means gas spring, ergonomic and adjustable seat, retractable seat belt, watertight hydraulic brakes, total control of movements with joystick integrating main functions, rotating beacon, rear-view mirror, emergency stop, anti-vandal protection and audible reverse warning.

DRIVING POSITION		
538.35 - AP/APG -	Full-Equip closed ROPS/FOPS cabin with heating including enhanced sound-proof and panoramic rear-mirrors.	11.280
538.30 - PLUS -	Homologated ROPS/FOPS driver protective folding roof. Folding assisted by gas springs.	1.940
743.10		
SAFETY		
744.02	Emergency stop on controls dashboard.	260
664.01	Disabling switch warning acoustic reverse.	110
745.51	Full visibility System through (FVS) front and rear cameras and TFT water-proof color 7" display for a total visibility and nightvision by infrared up to 10 m and obstacle sensors. (International metric system).	1.890
698.10	Reflective safety adhesives on rear body.	170
LIGHTING AND CIRCULATION		
618.61	Work headlighths (2 front + 1 rear).	720
319.15 - AP -	Homologated lighting system.	1.640
319.16 - APG -		
759.01	Max. 20 km/h speed limitation.	210
470.26	AUSTRIA circulation regulation - Homologated lighting system included.	3.340
470.29	GERMANY circulation regulation - Homologated lighting system included.	2.030
470.25	SWITZERLAND circulation regulation - Homologated lighting system included.	2.030
COMFORT		
526.04	Great comfort seat with total regulation.	690
ACCESSORIES		

690.30 APG	Northern countries	Specification for northern countries (more powerful heater. antifreeze and oil for low temperature and fuel filter water).	300
670.01	Documents	Water-tight case for operation and maintenance manuals.	170
619.80	Towing	Towing hitch (Rockinger).	1.040
620.30		Electric take-off for towing - COMPULSORY lighting system.	300
535.22	Protector	Front rubber fender.	350
696.20		Fan grid.	220
741.11	Air filter	Cyclonic air filter.	190
ACOL	Paint	Special paint colour (only parts in orange).	1.070
646.10	Environment	Bio Hydraulic Fluid environmentally friendly.	1.940
TRANSPORT			
802.10		Partial removal of the dumper for shipping in 40' container.	980
999.99		Photos for customs.	110
ADHESIVE LANGUAGE AND MANUALS			
D 1000 AP - KUBOTA			
465.55 - Deutz -		Adhesive plates in English.	0
467.14		Adhesive plates in French.	0
D 1000 APG - KUBOTA			
467.16 AP		Adhesive plates in English.	0
467.09 APG			
465.84 AP		Adhesive plates in French.	0
465.72 APG			
REGIONAL REGULATIONS			
D 1000 A - DEUTZ			
467.11		French finish.	70
465.58 -Deutz-		German finish.	0
465.93		UK finish.	0
465.58		Swiss finish.	0
D 1000 A - KUBOTA			
467.02		French finish.	70
465.71 -Kubota-		German finish.	0
465.86		UK finish.	0
465.71		Swiss finish.	0
PARTS			
800.04		Spare wheel (1ut) - Standard.	1.600
777.51 - Kubota -		Maintenance kit (1000h).	850
777.82 - Deutz -			

GENERAL CONDITIONS OF SALE

- 1. PREAMBLE:** The following conditions apply to all products offered (new or used) services and parts manufactured or distributed by AUSA. The placing of an order implies that the purchaser accepts these Terms and Conditions, with the exclusion of all others.
- 2. PURCHASE ORDER:** Any purchase order received by AUSA is subject to confirmation in writing, where the configuration and final price as well as the expected date of delivery in Manresa (Spain) will be indicated. The data on the order confirmation prevails over any prior information.
- 3. PRICE OF THE MACHINES:** The general price conditions are EX-WORKS (EXW - Incoterms 2010) and are expressed in Euros, unless otherwise indicated. The price does not include any direct or indirect tax, which will be paid by the buyer.
- 4. TERMS:** The delivery times indicated on the order confirmation are approximate and may not give rise to penalties for any delays or damages. Should the order include special accessories not included in the current list price, the buyer cannot use this reason to cancel the order.
- 5. MODIFICATION AND CANCELLATION OF PURCHASE ORDER:** Once the purchase order is confirmed, no change in the configuration or cancellation of the order can be made without prior written authorisation from the AUSA Sales Director. To request the modification or cancellation, the purchaser must submit a written authorization addressed to the person responsible for your account at AUSA. If approved, 20% of the import of the machines will be withheld in the concept of participation in logistics costs, quality management and restocking. Machinery orders or special accessories not included in the current price list will not be subject to any modification or cancellation.
- 6. COMPLAINTS AND WARRANTY:** Any complaints about the non-conformity of the products received in connection with products supplied must be carried out according to the channels and deadlines established (KMO claim). The buyer expressly acknowledges having received and accepted the terms of our warranty policy.
- 7. RETURNS:** The return of machines will not be accepted without prior written authorisation from the AUSA Sales Director. To request the refund, the purchaser must submit a written authorization addressed to the person responsible for your account at AUSA. If approved, 20% of the import of the machines will be applied. Transportation to the place of production will be paid by the purchaser. Also, the machines must be delivered with the original configuration and in perfect conditions, without being used. If the machines are received in poor conditions, AUSA is entitled to pass on these costs after receiving the AUSA product. Machine orders or special accessories not included in the current price list shall not be subject to any modification or cancellation.
- 8. PAYMENT:** Except where otherwise stipulated, invoices must be paid in advance with 20% at the time of order and 80% before collection in AUSA. In case of an authorized delayed payment the period shall begin on the date of the invoice. Orders for special accessories or special machines may not be subject to any payment deferment. The obligatory place of payment will be AUSA Center, S.L.U., unless otherwise agreed.
- 9. DELAYS:** Any delays in payment, automatically and without notice, will result in a default interest of 1% per month of delay, calculated on the amount owed and the period between the due date and the date the payment is received. The default of a debtor to a deadline after prior agreement extension makes all our debt immediately payable. This default will result in automatic termination of contracts and orders.
- 10. OWNERSHIP:** Ownership of the product will be AUSA until 100% of the amount of the invoice issued has been paid. In case of insolvency, bankruptcy or liquidation for the purchaser, AUSA acquires the right to recover goods supplied as collateral to receive outstanding payments.
- 11. DATA PROTECTION:** In compliance with the Personal Data Protection Regulations and thus, in accordance with the Spain Organic Law 15/1999, dated 13th December 1999, on the Protection of Personal Data (LOPD), we inform you that the contact details hereby provided are included in a file owned by AUSA Center, S.L.U.. Notwithstanding the aforementioned, you are acknowledged to have and may exercise the rights of access, cancellation, rectification and opposition, by writing to ausa@ausa.com or to AUSA Center, S.L.U., Ctra. de Vic, Km. 2,8, 08243 Manresa, Spain.
- 12. APPLICABLE LAW:** The contract is subject to the United Nations Convention on Contracts for the International Sale of Goods, 11th of April 1980 (CISG) regardless of whether the purchaser is resident in a CISG state or not. Additionally the Spanish law is applicable without recourse to its conflict-of-laws rules. The conclusion of this contract is subject exclusively to the Spanish law without recourse to its conflict-of-law rules and excluding the CISG.
- 13. JURISDICTION:** Any dispute concerning the interpretation and / or execution of these conditions of sale shall be sent to the Courts of the City of Manresa (Spain), unless otherwise agreed.

COMPANY ADDRESS: AUSA Center, S.L.U. - C/ Castelladral 1 - 08243 Manresa – Province of Barcelona – Spain, registered in the Mercantile Registry of Barcelona, T.38.109 - F.222- H. B-318.215 - INSC 11a.





AUSA
C/ Castelladral 1
08243 Manresa - Barcelona
SPAIN
Tel. +34 93 874 7311
ausa@ausa.com
www.ausa.com

AUSA Spain: +34 91 669 00 06 ausa.madrid@ausa.com
AUSA France: +33 (0) 4 68 54 38 97 - ausa.france@ausa.fr
AUSA U.K.: +44 (0)7703 60 9009 - ausa.uk@ausa.com
AUSA Central Europe: +49 2384 9415725 - info@ausa.de
AUSA Brasil: +55 11 40146906 - ausa.brasil@ausa.com
AUSA U.S.: +1 (310) 426 2305 - ausa.us@ausa.com
AUSA CHINA: +86 10 8598 7386 - ausa.china@ausa.com



www.ausa.com